



NIPPLI DA TUBO A BOTTIGLIA

3000 - 6000 LBS

SWAGE NIPPLES

3000 - 6000 LBS

Diam. nominale Nominal pipe size A x B	3000 - 6000				Spessore conforme a ANSI B 36-10-1985 Thickness according to ANSI B 36-10-1985		
	K ⁽¹⁾		L ⁽¹⁾				
	mm	inches	mm	inches			
3/8" x 1/4"	76	2.36	20	0.79	Sch 40	Sch 80	-
1/2" x 3/8"	89	2.36	20	0.79	Sch 40	Sch 80	-
1/2" x 1/4"	89	2.36	20	0.79	Sch 40	Sch 80	-
3/4" x 1/2"	95	2.75	21	0.83	Sch 40	Sch 80	Sch 160
3/4" x 1/4"	95	2.75	21	0.83	Sch 40	Sch 80	-
1" x 3/4"	102	3.55	22	0.87	Sch 40	Sch 80	Sch 160
1" x 1/2"	102	3.55	22	0.87	Sch 40	Sch 80	Sch 160
1" x 1/4"	102	3.55	25	0.98	Sch 40	Sch 80	Sch 160
1 1/4" x 1"	114	4.53	25	0.98	Sch 40	Sch 80	Sch 160
1 1/2" x 1"	114	4.53	25	0.98	Sch 40	Sch 80	Sch 160
1 1/2" x 3/4"	114	4.53	25	0.98	Sch 40	Sch 80	Sch 160
1 1/2" x 1/2"	165	6.50	30	1.18	Sch 40	Sch 80	Sch 160
2" x 1 1/2"	165	6.50	30	1.18	Sch 40	Sch 80	Sch 160
2" x 1"	165	6.50	30	1.18	Sch 40	Sch 80	Sch 160
2 1/2" x 2"	178	7.01	35	1.38	Sch 40	Sch 80	Sch 160
3" x 2"	203	8.00	40	1.57	Sch 40	Sch 80	Sch 160
4" x 3"	229	9.06	45	1.77	Sch 40	Sch 80	Sch 160
4" x 2"	229	9.06	45	1.77	Sch 40	Sch 80	Sch 160

⁽¹⁾ Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.
Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1

NOTE - NOTES:

Estremità a saldare secondo ANSI B 16.25 – *Buttwelding ends according to ANSI B 16.25*

Estremità filettate secondo ANSI B 1.20.1 – *Thread ends according to ANSI B 1.20.1*

Tolleranze su diametro e spessore secondo ASTM A 106 – *Variations in outside diameter and thickness according to ASTM A 106*