



MEZZI MANICOTTI S.W.

ANSI B 16.11
3000 - 6000 LBS

HALF-COUPPLINGS S.W.

ANSI B 16.11
3000 - 6000 LBS

| Diam. nominale Nominal pipe size | Coste di montaggio / Laying lengths | | | | | | | | | | | |
|-------------------------------------|-------------------------------------|--------|------|--------|------------------------------|--------|--------------------------------------|--------|------|--------|------------------------------|--------|
| | Manicotti / Couplings - E | | | | | | Mezzi manicotti / Half couplings - F | | | | | |
| | 3000 | | 6000 | | Tolleranze ± Tolerances ± | | 3000 | | 6000 | | Tolleranze ± Tolerances ± | |
| | mm | inches | mm | inches | mm | inches | mm | inches | mm | inches | mm | inches |
| 1/4" | 6.5 | 0.25 | 6.5 | 0.25 | 1.5 | 0.06 | 16.0 | 0.62 | 16.0 | 0.62 | 1.0 | 0.03 |
| 3/8" | 6.5 | 0.25 | 6.5 | 0.25 | 3.0 | 0.12 | 17.5 | 0.69 | 17.5 | 0.69 | 1.5 | 0.06 |
| 1/2" | 9.5 | 0.38 | 9.5 | 0.38 | 3.5 | 0.12 | 22.5 | 0.88 | 22.5 | 0.88 | 1.5 | 0.06 |
| 3/4" | 9.5 | 0.38 | 9.5 | 0.38 | 3.5 | 0.12 | 23.5 | 0.94 | 23.5 | 0.94 | 1.5 | 0.06 |
| 1" | 13.0 | 0.50 | 13.0 | 0.50 | 4.0 | 0.16 | 29.0 | 1.12 | 29.0 | 1.12 | 2.0 | 0.08 |
| 1 1/4" | 13.0 | 0.50 | 13.0 | 0.50 | 4.0 | 0.16 | 30.0 | 1.19 | 30.0 | 1.19 | 2.0 | 0.08 |
| 1 1/2" | 13.0 | 0.50 | 13.0 | 0.50 | 4.0 | 0.16 | 32.0 | 1.25 | 32.0 | 1.25 | 2.0 | 0.08 |
| 2" | 19.0 | 0.75 | 19.0 | 0.75 | 4.0 | 0.16 | 41.0 | 1.62 | 41.0 | 1.62 | 2.0 | 0.08 |
| 2 1/2" | 19.0 | 0.75 | 19.0 | 0.75 | 5.0 | 0.20 | 42.5 | 1.69 | 42.5 | 1.69 | 2.5 | 0.10 |
| 3" | 19.0 | 0.75 | 19.0 | 0.75 | 5.0 | 0.20 | 44.5 | 1.75 | 44.5 | 1.75 | 2.5 | 0.10 |
| 4" | 19.0 | 0.75 | 19.0 | 0.75 | 5.0 | 0.20 | 47.5 | 1.88 | 47.5 | 1.88 | 2.5 | 0.10 |

- Per quote B - C - D - G - J si vedano caratteristiche dimensionali a pag. 134
- For dimensions B - C - D - G - J refer to dimensions of s.w. fittings shown in page 134