



CROCI S.W.

ANSI B 16.11
3000 - 6000 LBS

CROSSES S.W.

ANSI B 16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	Dal centro alla base del raccordo A Center to bottom of socket A					
	3000		6000		Tolleranze ± Tolerances ±	
	mm	inches	mm	inches	mm	inches
1/4"	11.0	0.44	13.5	0.53	1.0	0.03
3/8"	13.5	0.53	15.5	0.62	1.5	0.06
1/2"	15.5	0.62	19.5	0.75	1.5	0.06
3/4"	19.5	0.75	22.5	0.88	1.5	0.06
1"	22.0	0.88	27.0	1.06	2.0	0.08
1 1/4"	27.0	1.06	32.0	1.25	2.0	0.08
1 1/2"	32.0	1.25	38.0	1.50	2.0	0.08
2"	38.0	1.50	41.0	1.62	2.0	0.08
2 1/2"	41.5	1.62			2.5	0.10
3"	57.5	2.25			2.5	0.10
4"	66.5	2.62			2.5	0.10

- Per quote B - C - D - G - J si vedano caratteristiche dimensionali a pag. 134
- For dimensions B - C - D - G - J refer to dimensions of s.w. fittings shown in page 134