



## RIDUZIONI FEMMINA-MASCHIO

ANSI B16.11  
3000 LBS

## FEMALE-MALE REDUCERS

ANSI B16.11  
3000 LBS

Diam. nominale Nominal pipe size	3000			
	M (1)		N (1)	
	mm	inches	mm	inches
3/8" x 1/4"	42	1.50	22	0.87
1/2" x 3/8"	49	1.81	28	1.10
1/2" x 1/4"	49	1.81	28	1.10
3/4" x 1/2"	59	2.01	35	1.38
1" x 3/4"	63	2.36	45	1.77
1" x 1/2"	61	2.36	45	1.77
1" x 1/4"	60	2.36	45	12.77
1 1/4" x 1"	68	2.68	60	2.24
1 1/2" x 1"	72	2.76	65	2.56
1 1/2" x 3/4"	67	2.76	65	2.56
1 1/2" x 1/2"	67	2.76	65	2.56
2" x 1/2"	70	2.95	76	2.99
2" x 1"	75	2.95	76	2.99
2 1/2" x 2"	92	3.74	95	3.74
3" x 2"	95	3.94	110	4.33
4" x 3"	113	4.33	140	5.51
4" x 2"	100	4.33	140	5.51

(1) Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.  
*Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.*

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1