



GOMITI 90°

ANSI B16.11
3000 - 6000 LBS

90° ELBOWS

ANSI B16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000						6000					
	A		H		G		A		H		G	
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches
1/4"	25	0.97	25	1.00	3.5	0.130	29	1.12	33	1.31	6.5	0.260
3/8"	29	1.12	33	1.31	3.5	0.138	33	1.31	38	1.50	7.0	0.275
1/2"	33	1.31	38	1.50	4.0	0.161	38	1.50	46	1.81	8.0	0.321
3/4"	38	1.50	46	1.81	4.5	0.170	44	1.75	56	2.19	8.5	0.336
1"	44	1.75	56	2.19	5.0	0.196	51	2.00	62	2.44	10.0	0.391
1 1/4"	51	2.00	62	2.44	5.5	0.208	60	2.38	75	2.97	10.5	0.417
1 1/2"	60	2.38	75	2.97	5.5	0.219	64	2.50	84	3.31	11.0	0.436
2"	64	2.50	84	3.31	7.0	0.281	83	3.25	102	4.00	12.0	0.476
2 1/2"	83	3.25	102	4.00	7.5	0.301	95	3.75	121	4.75	15.5	0.602
3"	95	3.75	121	4.75	9.0	0.348	106	4.19	146	5.75	16.0	0.655
4"	114	4.50	152	6.00	11.00	0.440	114	4.50	152	6.00	18.5	0.735

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1